

Technical Specification

Ventilation Modes

	A/C-V with sigh	A/C-P
	SIMV-V	SIMV-P
	SPONT/PSV	CPAP
		MANUAL

Parameters

• Tidal Volume:	0~2000 ml
• Respiration Rate:	1~120 bpm (A/C mode)
	1~40 bpm (SIMV mode)
• I:E Ratio:	1:10~4:1
• FiO ₂ :	40%~100%
• Trigger Sensitivity:	Pressure trigger: -20~0 cmH ₂ O
• Flow Trigger:	2~30 L/min
• PEEP:	0~30 cmH ₂ O

Monitoring

• Pressure Value:	Ppeak, PEEP
• Volume / Flow Value:	Vt, MV
• Time Value:	ftotal
• Real Time Curves:	Pressure-Time, Flow-Time

Alarms

Paw high	Paw low	MV high	Gas supply down
No VT	FiO ₂ high	FiO ₂ low	Apnea
Continuous pressure high / CP high			EX. power lost
O ₂ deficiency	Battery low		

Technical Data

• Supply Gas:	O ₂ , 0.25~0.6 MPa
• Power Supply:	AC100~240 V, 50 Hz/60 Hz, ≤65 VA
• Screen Size:	5" LCD Screen
• Maximum Security Pressure:	≤8 KPa
• Compliance:	≤4 ml / 100 Pa
• Dimension (WxDxH):	168 mm x 156 mm x 300 mm
• Battery Operating Time:	Approx. 4.5H
• Weight:	3.2 kg (Main unit)
	8 kg (Main unit & Accessories)

Remark: Above configurations include standard and optional. Please check price with your Aeonmed sales representative.



Shangrila510S Emergency Transport Ventilator

CE 0123

AEOMED
Reliable Quality Thoughtful Service

The information contained in this leaflet is correct at the date of publication. The policy of Beijing Aeonmed Co., Ltd. is one of the continued improvement to its products. Because of this policy, Aeonmed reserves the right to make any change, which may affect the information in this leaflet without giving prior notices.
AVT510S-1907

HQ: Building 9, No.26 Outer Ring West Road, Fengtai District, Beijing 100070, China
Science Park: No. 10, Chaobai Street, Yanjiao Development Zone, Sanhe City, Hebei Province 065201, China
TEL: +86-10-58411198 FAX: +86-10-83681616-8130
Http: //www.aeonmed.com/en E-mail: marketing@aeonmed.com

AEOMED
Reliable Quality Thoughtful Service



Shangrila 510S

Emergency Transport Ventilator

- Combines advanced technology and versatile ventilation functions
- Meets the breathing requirements of adults, pediatric and infant patients
- Pneumatically driven electronically controlled



Multi-functional Emergency Transport Ventilator

- It helps optimize quality of care & patient comfort, improving patient outcomes
- One device addresses diverse ventilation requirements, fully covering various situations

Integrated with Versatile Ventilation Modes

- Pressure control & Volume control mode
- Invasive & Non-Invasive ventilation
- SPONT/PSV, CPAP modes

Manual Intervention Functions

- Manual breath
- Inspiratory hold

Enhancements

- FiO₂ 40% to 100% continuously adjustable
- Waveform display: Pressure- time, Flow-time
- Alarm silence
- Pre-use test

Features

Simple operation, compact design, reliable performance



- Waveform display and multi-parameter monitoring
- Electronically controlled PEEP



- Acoustic and visual alarms
- Anti-crash design



- Direct access to critical settings and patient data



- Operate with low flow oxygen supply

Safety Guarantee

- Meets with EN1789 standard
- IPX4 waterproof level

Applications

Emergency – Transport – Intra-hospital transfer – Recovery



Multiple Ways of Power Supply

- Vehicle D/C power
- 4.5h long lasting internal battery
- A/C power adaptor
- External backup battery(optional)

Comprehensive Accessories

- Suction unit
- 2.8L Oxygen cylinder kit
- Oxygen sensor
- Hanging plate assembly